

PANEL SYSTEMS

MANUFACTURING SPECIFICATIONS:

Width	Number of Panels	
	ONE-WAY DRAW	CENTER OPENING
48"-84"	3 panels	4 panels
84½"-120"	4 panels	4 panels
120½"-180"	5 panels	6 panels

Stacking: Take coverage width, add total inches of overlaps (3" overlaps are provided to limit light seepage) and divide by number of panels.
Contact customer service for special requests. Please note, tracks come with 3 channels minimum and 5 channels maximum.

* For oversized widths, due to shipping, track may be required to come as two pieces installed next to one another with baton controls.
Contact customer service for special requests.

Upon special request, panel systems can come with 8 panels as a split draw:



Track	Minimum Depth to Install	Minimum Depth for flush Mount	Outside Mount Projection from Wall to Front of Track
3 Channel	1½"	2¼"	3"
4 Channel	2"	2¾"	3½"
5 Channel	2½"	3¾"	3¾"

*Extension brackets available upon special request to extend back of track up to 4½" off the wall

Track Depth	
3 Channel Tracks	2"
4 Channel Tracks	2½"
5 Channel Tracks	3¼"
Track Height	
5/8"	

Control Options	
Cord	Based on panel length
Wand	Based on panel length. Up to 72" long
Inside Mount Deduction	
3/8" Overall	
Provided Overlap	
3"	